

envirolay

Carpet underlay that treads lightly on the planet

TECHNICAL SPECIFICATION

ENVIROLAY 28

Roll Dimensions

Length (M)	Width (M)	Area (Sq.M)
11	1.37	15.07

Thickness	Weight	BS 5808	BS 4790
mm +/- 10%	g/m2 +/- 10%	Classification	Flammability
7	950	GD/U	Pass – Low Radius

Carbon Footprint per roll	BS 4745	BS EN ISO 140-8:1998
345g of co2/kg of product	Thermal Insulation	Impact Sound Reduction
4930g	2.42 Tog	-

Comfort/Durability	Recommendations		
6/10	Bedrooms	Living	Hall, Stairs & Landing
	*	✓	✓

Installation

Subfloors should be dry, clean and free of oil, grease & damp.

Fitting should meet the British Standard code of practice BS 5325 & be undertaken by experienced fitters.

✓ Suitable

* Highly Recommended



www.envirolay.co.uk

Please note: This document does not constitute a manufacturing specification. It details important technical performance and physical characteristics of the product only. Please contact the Technical Department for any further information.

Texfelt Ltd

Unit 2 Cutler Heights Business Park, Cutler Heights Lane,
Bradford, West Yorkshire BD4 9AQ. UK

Telephone +44 (0) 1274 905411 Facsimile +44 (0) 1274 905412

Email sales@textfelt.co.uk Website www.textfelt.co.uk