

Manufacturers and distributors of carpet  
underlays and flooring accessories



**envirolay**  
Carpet underlay that treads lightly on the planet

## TECHNICAL SPECIFICATION

### ENVIROLAY 33

---

#### Roll Dimensions

Length (M)	Width (M)	Area (Sq.M)
11	1.37	15.07

---

Thickness mm +/- 10%	Weight g/m2 +/- 10%	BS 5808 Classification	BS 4790 Flammability Pass – Low Radius
9.5	1120	HC/U	

---

Carbon Footprint per roll 345g of co2/kg of product 5810g	BS 4745 Thermal Insulation 2.79 Tog	BS EN ISO 140-8:1998 Impact Sound Reduction - 27dB
---	---	--

---

Comfort/Durability	Recommendations
7/10	Bedrooms *      Living *      Hall, Stairs & Landing *

---

#### Installation

Subfloors should be dry, clean and free of oil, grease & damp.

Fitting should meet the British Standard code of practice BS 5325 & be undertaken by experienced fitters.

---

✓ Suitable

\* Highly Recommended



[www.envirolay.co.uk](http://www.envirolay.co.uk)



---

*Please note: This document does not constitute a manufacturing specification. It details important technical performance and physical characteristics of the product only. Please contact the Technical Department for any further information.*

#### Texfelt Ltd

Unit 2 Cutler Heights Business Park, Cutler Heights Lane,  
Bradford, West Yorkshire BD4 9AQ. UK

Telephone +44 (0) 1274 905411 Facsimile +44 (0) 1274 905412

Email [sales@textfelt.co.uk](mailto:sales@textfelt.co.uk) Website [www.textfelt.co.uk](http://www.textfelt.co.uk)