

envirolay

Carpet underlay that treads lightly on the planet

TECHNICAL SPECIFICATION

ENVIROLAY 42

Roll Dimensions

Length (M)	Width (M)	Area (Sq.M)
11	1.37	15.07

Thickness mm +/- 10%	Weight g/m2 +/- 10%	BS 5808 Classification	BS 4790 Flammability Pass – Low Radius
11	1424	HC/U	

Carbon Footprint per roll 345g of co2/kg of product 7395g	BS 4745 Thermal Insulation 3.25 Tog	BS EN ISO 140-8:1998 Impact Sound Reduction - 33dB

Comfort/Durability	Recommendations
8/10	Bedrooms * Living * Hall, Stairs & Landing *

Installation

Subfloors should be dry, clean and free of oil, grease & damp.

Fitting should meet the British Standard code of practice BS 5325 & be undertaken by experienced fitters.

✓ Suitable

* Highly Recommended



www.envirolay.co.uk



Please note: This document does not constitute a manufacturing specification. It details important technical performance and physical characteristics of the product only. Please contact the Technical Department for any further information.

Texfelt Ltd

Unit 2 Cutler Heights Business Park, Cutler Heights Lane,
Bradford, West Yorkshire BD4 9AQ. UK

Telephone +44 (0) 1274 905411 Facsimile +44 (0) 1274 905412

Email sales@textfelt.co.uk Website www.textfelt.co.uk