

Manufacturers and distributors of carpet
underlays and flooring accessories



envirolay
Carpet underlay that treads lightly on the planet

TECHNICAL SPECIFICATION

ENVIROLAY 54

Roll Dimensions

Length (M)	Width (M)	Area (Sq.M)
11	1.37	15.07

Thickness mm +/- 10%	Weight g/m2 +/- 10%	BS 5808 Classification	BS 4790 Flammability Pass – Low Radius
13	1831	HC/U	

Carbon Footprint per roll 345g of co2/kg of product 9505g	BS 4745 Thermal Insulation 3.42 Tog	BS EN ISO 140-8:1998 Impact Sound Reduction - 35dB
---	--	--

Comfort/Durability	Recommendations
10/10	Bedrooms * Living * Hall, Stairs & Landing *

Installation

Subfloors should be dry, clean and free of oil, grease & damp.

Fitting should meet the British Standard code of practice BS 5325 & be undertaken by experienced fitters.

✓ Suitable

* Highly Recommended



we are a member of
needlefelt underlay
manufacturers association



www.envirolay.co.uk



Please note: This document does not constitute a manufacturing specification. It details important technical performance and physical characteristics of the product only. Please contact the Technical Department for any further information.

Texfelt Ltd

Unit 2 Cutler Heights Business Park, Cutler Heights Lane,
Bradford, West Yorkshire BD4 9AQ. UK

Telephone +44 (0) 1274 905411 Facsimile +44 (0) 1274 905412

Email sales@textfelt.co.uk Website www.textfelt.co.uk